

## Revolution

PRODUCT TYPE Hand Woven
CONSTRUCTION Woven

FIBER 100% New Zealand Wool or PET

DYE METHOD Skein Dye
PRIMARY BACKING Synthetic
SECONDARY BACKING Cotton Canvas

SIZES Custom

 $\begin{array}{lll} \mbox{Pile Height} & 0.375 \mbox{ in} & 9.5 \mbox{ mm} \\ \mbox{Total Height} & 0.375 \mbox{ in} & 9.5 \mbox{ mm} \\ \mbox{Yarn Weight} & 10.5 \mbox{ oz/ft}^2 & 3205 \mbox{ gm/m}^2 \\ \mbox{Total Weight} & 10.5 \mbox{ oz/ft}^2 & 3205 \mbox{ gm/m}^2 \end{array}$ 

## Lead Time 10 Weeks + Transit Made in India

## **Performance + Testing**

CLIENT	Art of Floors

TEST METHOD CONDUCTED Surface Flammability of Carpets and Rugs (16 CFR Chapter II, Subchapter D, Part 1630 CPSC FF I-70), also referenced as ASTM D2859

DESCRIPTION OF TEST SAMPLE	
IDENTIFICATION	Custom Rug Sample
CONSTRUCTION	Cut Pile
BACKING	Woven
Diteiting	

## **Warranties**

Warranty and cleaning information available upon request

